

Contact(s)

Name	Email	Phone	Skype
Uwe Bach	ubach at mpifr.de	+49 2257 301168	

Recorder(s)

Mark5B+ (DBBC)	OS	Debian 4.0 etch
	SDK	9.2
	software version	jive5ab 2.5.0
Mark5C (RDBE)	OS	Debian 5.0 lenny
	SDK	9.2
	software version	DRS 0.9.9-1

Mark 6 used as Flexbuff, connected to the DBBC2. The data will be transferred to the Bonn correlator by fibre.

Backend(s)

DBBC 2	<p>PFB firmware version: V14</p> <p>DDC firmware version: v104</p> <p>FILA10G firmware version: currently in Bonn</p> <p>Hardware: 4 IF inputs, ADB1, 4xCore2Boards, CAT2</p>
RDBE	<p>PFB firmware version: pfb_1.4.2</p> <p>DDC firmware version: ddc_1501383</p> <p>NRAO soft-switch to join two RDBEs to Mark5C</p> <p>Hardware: 2 RDBEs with 2 IF inputs each. Can use 1 RDBE in PFB mode at 2 Gbps (16x32MHz) or 2 RDBEs with 8 individual BBCs at band width from 1 to 64 MHz either USB or LSB.</p>

Field System

Version	9.11.5
---------	--------

Activity Log